



**All Tica reels
are available —
24-48 hour shipping**

SCRAMBER SS SERIES

- 6 precision stainless steel ball bearings
- Cybernetic Frame system (CF)
- Titanium plated anti-twist line roller
- Instant anti-reverse
- Aluminum alloy reel body, rotor and spool
- Balanced anti-twist rotor
- Intelligent Oscillating system (I/O)
- Soft-touch handle knob

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICASS2000R	5.2	10.6	6BB+1RB	28.3 in.	5/225, 6/175, 8/135
TICASS2500R	5.2	10.6	6BB+1RB	28.3 in.	6/220, 8/175, 10/160
TICASS3500R	5.2	14.3	6BB+1RB	31.1 in.	10/220, 12/200, 14/170
TICASS4000R	5.2	14.3	6BB+1RB	31.1 in.	12/260, 14/230, 17/200
TICASS5000R	4.3	22	6BB+1RB	31.1 in.	14/350, 17/290, 18/220
TICASS6000R	4.3	22	6BB+1RB	31.1 in.	17/360, 18/280, 20/220
TICASS7000R	4.1	26.6	6BB+1RB	33.5 in.	18/310, 20/240, 25/200
TICASS8000R	4.1	26.8	6BB+1RB	33.5 in.	20/280, 25/230, 30/200
TICASS10000R	4.1	25.7	6BB+1RB	33.8 in.	25/355, 30/290, 35/245



WASABI WC SERIES

- 8 precision stainless steel rust resistant ball bearings
- One piece aluminum frame CNC machined
- Centrifugal brake system
- Quick remove sideplate
- Forged aluminum alloy handle knob
- Forged aluminum alloy spool
- Instant anti-reverse
- Star drag
- Line out alarm

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICAWC205	5.2	13.3	8BB+1RB	23.2 in.	14/275, 17/210, 20/165



STRIPER LE SERIES

- 8 precision stainless rust resistant ball bearings
- One piece aluminum frame CNC machined
- Centrifugal brake system
- Quick remove sideplate
- Large ultra wear-resisting line guide
- Forged aluminum alloy spool
- Instant anti-reverse
- Star drag
- Line out alarm
- Forged aluminum alloy handle knob

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICALE200	5.2	14.6	8RRB+1RB	23.2 in.	14/275, 17/210, 20/165



ALASKAN AK SERIES

- 4 rust resistant ball bearings and 2 SUS ball bearings
- One piece aluminum frame CNC machined
- Centrifugal brake system
- Quick remove sideplate
- Large ultra wear-resisting line guide
- Forged aluminum alloy spool
- Instant anti-revers
- Star drag
- Line out alarm
- Soft-touch handle knob & clutch bar

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICAAK50BLUE	5.2	12	4RRB+2BB(SUS)+1RB	23.2 in.	14/275, 17/210, 20/165
TICAAK51BLUE	5.2	12	4RRB+2BB(SUS)+1RB	23.2 in.	14/275, 17/210, 20/165



Sea Striker® Reels

CORVUS LEVELWIND REEL

No.	Description
SEACC20	2BB - 4.1-1 gear ratio - 310 yds 20# mono
SEACC30	2BB - 4.4-1 gear ratio - 325 yds 20# mono

ARIES SPINNING REELS

No.	Description
SEAAS40	4+1 BB - 5.2-1 gear ratio - 215 yds 10# mono
SEAAS50	4+1 BB - 5.2-1 gear ratio - 300 yds 12# mono
SEAAS60	4+1 BB - 5.2-1 gear ratio - 250 yds 15# mono
SEAAS70	4+1 BB - 4.1-1 gear ratio - 350 yds 20# mono



**Combos are
also available.
Call for models.**