

All Tica reels are available —
24-48 hour shipping



See our website for complete listing and color catalog, or call for info.



LIBRA SA SERIES SPINNING

- 10 pcs precision ball bearings
- Mini bearing inside of line roller
- Forged aluminum alloy spool
- Computer designed balanced rotor to minimize vibration
- Coiled bail spring
- High tensile strength graphite body

- Instant anti-reverse
- One touch handle
- Right/left interchangeable handle
- Soft touch handle knob
- Stainless steel cover A & B on rotor right/left sides, titanium plated
- Stainless steel spool lip, titanium plated

- Anti-twist line roller, titanium plated
- Worm shaft system
- Aluminum spool decorated with 24 wave motion type conk holes
- Anti-twist rotor
- Power drive gear equipped for strength and smoothness (only for 3500/4000)



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICASA2500	5.2	10.2	10	1	25.0	5/150, 6/110, 8/82
TICASA3000	5.2	10.7	10	1	27.0	6/165, 8/130, 10/110
TICASA3500	5.2	14.8	10	1	30.9	10/250, 12/230, 14/205
TICASA4000	5.2	15.3	10	1	33.4	12/300, 14/260, 17/215

CYBERNETIC GG100 SERIES (GG-R)

- Cybernetic Frame System(CF)
- 8 precision stainless ball bearings
- Aluminum spool
- Titanium plated anti-twist line roller
- Computer designed balanced rotor

- Instant anti-reverse
- Mini bearing inside the line roller
- Ambidextrous
- Comfortable handle knob with 2BB
- Lifetime bail spring

- Intelligent oscillating system(I/O)
- 90mm extra long handle arm for powerful retrieve



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICAGG100	3.3	30.3	8	1	34.8	20/480, 25/390, 30/330, 40/230

SCEPTER GX SERIES

No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICAGX8000	5.2	23.5	5	1	45	17/405, 20/240, 25/200
TICAGX9000	5.2	23.5	5	1	45	20/305, 25/250, 30/205
TICAGX10000	5.2	23.5	5	1	45	25/285, 30/235, 35/200





All Tica reels are available — 24-48 hour shipping

SPORTERA SR SERIES SPINNING (Live Bait Fishing Series) (SR-R)

- 7 pcs precision ball bearings
- Aluminum spool
- Computer designed balanced rotor to minimize vibration
- Instant anti-reverse
- Mini bearing inside of anti-twist line roller, titanium plated
- Right/left interchangeable handle
- Non slip handle knob
- Stainless steel main shaft
- Hit and run system
- Hit and run tension adjustment screw is precision machine cut
- Hit and run tension adjusting knob
- Free spool line out alarm
- Anti-twist roller
- Worm shaft system
- Power drive gear equipped for higher strength and better smoothness



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICASR4007	5.2	18.0	7	1	33.4	12/300, 14/270, 17/220
TICASR4507	5.2	18.3	7	1	36.0	14/330, 17/270, 20/180
TICASR5007	4.4	22.4	7	1	32.0	17/300, 20/240, 25/200
TICASR6007	4.4	22.9	7	1	34.0	20/270, 25/220, 30/180

SPINFOCUS GT SERIES SPINNING REEL (GT-R)

- 6 precision stainless rust resistant ball bearings
- Computer designed balanced rotor
- Titanium plated anti-twist line roller
- Anti-twist rotor
- Soft-touch power handle knob with 2 stainless steel bearings
- Coiled bail spring
- Instant anti-reverse
- Ambidextrous
- Crank Oscillating System (on 3000, 3500, 6000, 7000)
- Intelligent Oscillating System (on 1000, 2000, 2500, 4000, 4500)
- Two-toned anodized aluminum spool and rear body



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICAGT3000	5.2	11.3	6	1	30.9	10/220, 12/195, 14/165
TICAGT3500	5.2	12.0	6	1	34.0	12/260, 14/215, 17/165
TICAGT4000	5.2	15.7	6	1	37.3	14/270, 17/220, 20/170
TICAGT4500	5.2	16.2	6	1	40.5	17/270, 20/220, 25/180
TICAGT6000	4.3	23.6	6	1	36.2	20/310, 25/250, 30/210
TICAGT7000	4.3	24.7	6	1	39.0	20/360, 25/300, 30/240

SPINFOCUS GK (FRONT DRAG) SPINNING REEL (GK-R)

- 6 precision stainless rust resistant ball bearings
- Computer designed balanced rotor
- Titanium plated anti-twist line roller
- Anti-twist rotor
- Soft-touch power handle knob
- Coiled bail spring
- Instant anti-reverse
- Ambidextrous
- Crank Oscillating System (on 3000, 3500, 6000, 7000)
- Intelligent Oscillating System (on 1000, 2000, 2500, 4000, 4500)
- Two-toned anodized rear body cover
- Aluminum alloy spool



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICAGK2000	5.2	10.2	2	1	29.0	5/225, 6/175, 8/135
TICAGK3000	5.2	11.1	2	1	30.9	10/220, 12/195, 14/165
TICAGK3500	5.2	11.8	2	1	34.0	12/260, 14/215, 17/165
TICAGK4000	5.2	15.5	2	1	37.3	14/270, 17/220, 20/170
TICAGK4500	5.2	16.0	2	1	40.5	17/270, 20/220, 25/180
TICAGK6000	4.4	23.5	2	1	36.2	20/310, 25/250, 30/210
TICAGK7000	4.4	24.5	2	1	39.0	20/360, 25/300, 30/240

CETUS 500 SPINNING

- 6(SS/SB) 4(GV) 2(LF) precision stainless steel ball bearings
- Mini bearing inside the line roller
- Computer designed balanced rotor
- Instant anti-reverse
- Ambidextrous
- Titanium Anti-twist line roller
- Soft touch handle knob with 2 stainless steel ball bearings (only SS/SB)
- Extra spool
- Aluminum alloy
- Aluminum spool decorated with 18 conk holes on the SS500



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICASS500	5.2	6.3	6	1	20.2	4/95, 6/60, 8/50
TICASB500	5.2	6.3	6	1	20.2	4/95, 6/60, 8/50
TICAGV500	5.2	6.3	4	1	20.2	4/95, 6/60, 8/50
TICALF500	5.2	6.3	2	1	20.2	4/95, 6/60, 8/50

All Tica reels
are available —
24-48 hour shipping



TICA TEAM BIG GAME TROLLING

- Line out alarm
- One piece aluminum frame, spool and sideplate
- Two-speed shifting system for easy switching the gear ratio
- Dual drag system gives you both powerful, smooth and even drag performance
- 6 sealed stainless steel ball bearings
- Stainless steel gears / shaft
- Waterproofing system
- Forged and anodized super rigid aluminum alloy reel seat
- Multi anti-reverse mechanism for better durability
- Drag lever system provides handy drag control from "Free" to "Full" 150° of drag setting



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICA12WTS	4.7/2.3	40.5	6	—	—	12/740
TICA16WTS	4.4/2.0	44.4	6	—	—	16/640
TICA20WTS	4.4/2.0	50.0	6	—	—	20/820
TICA30WTS	3.8/1.8	66.0	6	—	—	30/900
TICA50WTS	3.2/1.3	77.0	6	—	—	50/850

TICA TEAM ST SERIES (ST-R)

Versatile in live bait casting, light trolling or iron jig fishing. Features 6 sealed stainless steel ball bearings and a powerful tempered stainless steel gears and pinion. Smooth and superb drag design.

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve		Line Cap. (lb-yds)
				Per Turn		
TICAST458G	4.2	26.2	6BB+2RB	30.1 in.		17/620, 20/375, 25/300
TICAST558G	4.2	27.5	6BB+2RB	30.1 in.		17/760, 20/460, 25/370, 30/305
TICAST468G	3.7	29.0	6BB+2RB	31.1 in.		17/860, 20/520, 25/420, 30/350
TICAST568G	3.7	29.6	6BB+2RB	31.1 in.		20/640, 25/520, 30/430, 40/305
TICAST668G	3.7	31.0	6BB+2RB	31.1 in.		20/870, 25/700, 30/580, 40/415



SCULPTOR SL SERIES BAITCASTING

- 12 pcs precise ball bearings
- Forged aluminum alloy spool
- One piece aluminum frame processed with the precise CNC machinery, provides strength and rigidity
- Instant anti-reverse
- Star drag lever with click
- Magforce brake system can be easily operated with single finger
- Low profile design
- Single screw lock frame & right side cover, easy to operate
- Attractive and delicate pattern is engraved with laser
- Soft-touch handle knob & casting bar
- For fresh water angling only



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICASL100	5.2	9.8	12	1	28.3	8/175, 10/160, 12/150, 14/130
TICASL100H	6.2	10.0	12	1	23.6	8/120, 10/110, 12/105, 14/95
TICASL101*	5.2	9.8	12	1	28.3	8/175, 10/160, 12/150, 14/130
TICASL101H*	6.2	10.0	12	1	23.6	8/120, 10/110, 12/105, 14/95

CAIMAN CJ-R SERIES

- 10 RRB (Rust resistant bearings)
- Forged aluminum alloy spool
- One piece aluminum frame CNC machined
- Instant anti-reverse
- Centrifugal brake system
- Star drag
- Single screw locking frame
- Soft-touch casting bar
- Line out alarm
- Aluminum line guide
- Waterproof handle side cover
- Forged aluminum alloy handle knob

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve		Line Cap. (lb-yds)
				Per Turn		
TICACJ200BLUE	5.2	14.6	10BB+1RB	23.2 in.		14/275, 17/210, 20/165
TICACJ200WINE	5.2	14.6	10BB+1RB	23.2 in.		14/275, 17/210, 20/165





All Tica reels are available — 24-48 hour shipping

CAIMAN DJ SERIES

- 10 RRB (Rust resistant bearings) and 2 SUS ball bearings
- Forged aluminum alloy spool
- One piece aluminum frame CNC machined
- Instant anti-reverse
- Centrifugal brake system
- Star drag
- Single screw locking frame
- Soft-touch casting bar
- Line out alarm
- Aluminum line guide
- Waterproof handle side cover
- Forged aluminum alloy handle knob



No.	Gear		Line Retrieve		Line Cap. (lb-yds)
	Ratio	Wt. (oz.)	Bearings	Per Turn	
TICADJ100	5.2	10.4	10RRB+2BB+1RB	18.8 in.	10/205, 12/140, 14/105
TICADJ150	5.2	11.3	10RRB+2BB+1RB	21.8 in.	12/205, 14/175, 17/150
TICADJ200	5.2	12.2	10RRB+2BB+1RB	23.2 in.	14/275, 17/210, 20/165

CAIMAN GJ SERIES

- 10 rust resistant ball bearings and 2 SUS ball bearings
- Forged aluminum alloy spool
- One piece aluminum frame CNC machined
- Instant anti-revers
- Centrifugal brake system
- Star drag
- Single screw locking frame
- Soft-touch clutch bar
- Line out alarm
- Aluminum line guide
- Water proof handle side cover
- Forged aluminum alloy handle knob



No.	Gear		Bearings	Handle Turn (in)	Line Retrieved Capacity lb/yds
	Ratio	Wt. (oz.)			
TICAGJ100M	5.2	10.4	10RRB+2BB(SUS)+1RB	18.8	5/205, 6/160, 8/125
TICAGJ101M	5.2	10.4	10RRB+2BB(SUS)+1RB	18.8	5/205, 6/160, 8/125
TICAGJ150M	5.2	11.3	10RRB+2BB(SUS)+1RB	21.8	6/215, 8/170, 10/150
TICAGJ151M	5.2	11.3	10RRB+2BB(SUS)+1RB	21.8	6/215, 8/170, 10/150
TICAGJ200	5.2	12.2	10RRB+2BB(SUS)+1RB	23.2	14/275, 17/210, 20/165
TICAGJ201	5.2	12.2	10RRB+2BB(SUS)+1RB	23.2	14/275, 17/210, 20/165

CAIMAN GT SERIES

- 4 rust resistant ball bearings and 2 SUS ball bearings
- Forged aluminum alloy spool
- One piece aluminum frame CNC machined
- Instant anti-revers
- Centrifugal brake system
- Star drag
- Single screw locking frame
- Soft-touch handle knob and clutch bar
- Line out alarm
- Aluminum line guide
- Water proof handle side cover



No.	Gear		Bearings	Handle Turn (in)	Line Retrieved Capacity lb/yds
	Ratio	Wt. (oz.)			
TICAGT100M	5.2	9.9	4RRB+2BB(SUS)+1RB	18.8	5/205, 6/160, 8/125
TICAGT101M	5.2	9.9	4RRB+2BB(SUS)+1RB	18.8	5/205, 6/160, 8/125
TICAGT150M	5.2	10.7	4RRB+2BB(SUS)+1RB	21.8	6/215, 8/170, 10/150
TICAGT151M	5.2	10.7	4RRB+2BB(SUS)+1RB	21.8	6/215, 8/170, 10/150
TICAGT200	5.2	11.6	4RRB+2BB(SUS)+1RB	23.2	14/275, 17/210, 20/165
TICAGT201	5.2	11.6	4RRB+2BB(SUS)+1RB	23.2	14/275, 17/210, 20/165

SEA WAVE SW SERIES

- 6 sealed precision stainless steel ball bearings
- Oversized smooth drag washers
- Star drag
- Aluminum alloy frame and sideplate
- Forged aluminum spool
- Line out alarm
- Free-spin spool control knob
- High strength brass pinion gear
- Stainless steel pinion gear, reel seat, and casting bar



No.	Gear Ratio	Wt. (oz.)	Bearing		Line Retrieved Handle Turn (in)	Capacity lb/yds
			B.B.	R.B.		
TICASW458VH	6.2	21.7	6	1	40.5	17/475, 20/375, 25/300
TICASW558VH	6.2	22.2	6	1	40.5	17/580, 20/460, 25/370, 30/305
TICASW468VH	6.2	23.6	6	1	47.2	17/660, 20/520, 25/420, 30/350
TICASW568VH	6.2	24.1	6	1	47.2	20/640, 25/520, 30/430, 40/305

* Left handed model

All Tica reels
are available —
24-48 hour shipping



SEASPIRIT SS SERIES (SS-R)

- Forged Aluminum Spool. High density and rigid forged aluminum spool for strength and durability. Ball Bearings are mounted on each side of the spool for smooth performance.
- Quick Sideplate Removal. Quick remove side plate for easy change of spool
- Ergonomic Designed Power Handle can be adjusted to suit the cranking power needed to fight stubborn fish.
- 5 Sealed Ball Bearings and One Way Clutch Bearing. Super smooth bearings and impact resistant one way clutch bearing during fish strike.
- Oversized Drag Washer provides smoother performance and more precise drag adjustment.



No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICASS248	5.1	17.6	5BB+1RB	29.5 in.	14/390, 17/320, 20/200
TICASS348	5.1	18.0	5BB+1RB	29.5 in.	17/430, 20/260, 25/210
TICASS458	4.2	22.2	5BB+1RB	28.0 in.	17/620, 20/375, 25/300
TICASS558	4.2	22.5	5BB+1RB	28.0 in.	17/760, 20/460, 25/370, 30/305

SEASPIRIT SP SERIES (SP-R)

- Ergonomic Designed Power Handle can be adjusted to suit the cranking power needed to fight stubborn fish.
- Quick Sideplate Removal. Quick remove side plate for easy change of spool
- Oversized Drag Washer provides smoother performance and more precise drag adjustment.



No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICASP248	5.1	16.6	2BB	29.5 in.	14/390, 17/320, 20/200
TICASP348	5.1	17.0	2BB	29.5 in.	17/430, 20/260, 25/210
TICASP458	4.2	20.8	2BB	28.0 in.	17/620, 20/375, 25/300
TICASP558	4.2	21.1	2BB	28.0 in.	17/760, 20/460, 25/370, 30/305

VETERAN T SERIES (T-R)

- Forged aluminum frame/spool/stand/drag knob/processed by CNC machine.
- Power drag control system.
- 4 precision stainless steel ball bearings.
- One-touch release spool.
- Wooden handle knob.
- Balanced spool.
- Line out alarm.
- Oversized drag washer.
- One way clutch roller bearing.
- Ambidextrous.
- Reel bag.



No.	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)	Spool Size (dia/wide)/mm
TICAT206	5.8	4BB+1RB	9.5 in.	WF6F+45 yds/12 lb	84.0/25
TICAT208	6.0	4BB+1RB	9.5 in.	WF8F+70 yds/20 lb	84.0/30
TICAT209	6.3	4BB+1RB	10.8 in.	WF9F+110 yds/20 lb	95.0/27
TICAT211	7.3	4BB+1RB	11.7in.	WF11F+220 yds/30 lb	102.0/32

VETERAN S SERIES (S-R)

- Forged aluminum frame/stand/processed by CNC machine.
- Balanced spool.
- Power drag control system.
- 2 precision stainless steel ball bearings.
- One-touch release spool.
- Wooden handle knob.
- Aluminum spool.
- Line out alarm.
- Oversized drag washer.
- One way clutch roller bearing.
- Ambidextrous.
- Reel bag.



No.	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)	Spool Size (dia/wide)/mm
TICAS206	5.6	2BB+1RB	9.5 in.	WF6F+45 yds/12 lb	84.0/25
TICAS208	5.8	2BB+1RB	9.5 in.	WF8F+70 yds/20 lb	84.0/30
TICAS209	6.7	2BB+1RB	10.8 in.	WF9F+110 yds/20 lb	95.0/27
TICAS211	7.4	2BB+1RB	11.7in.	WF11F+220 yds/30 lb	102.0/32

VETERAN G SERIES (G-R)

- Aluminum frame/spool/stand CNC machined.
- Line out alarm.
- Oversized drag washer.
- One way clutch roller bearing.
- Ambidextrous.
- Reel bag.
- Balanced spool.
- Power drag control system.
- 1 precision stainless steel ball bearing.
- One-touch release spool.
- Wooden handle knob.



No.	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)	Spool Size (dia/wide)/mm
TICAG206	5.6	1BB+1RB	9.5 in.	WF6F+45 yds/12 lb	84.0/25
TICAG208	6.0	1BB+1RB	9.5 in.	WF8F+70 yds/20 lb	84.0/30
TICAG209	6.7	1BB+1RB	10.8 in.	WF9F+110 yds/20 lb	95.0/27
TICAG211	7.6	1BB+1RB	11.7in.	WF11F+220 yds/30 lb	102.0/32



**All Tica reels
are available —
24-48 hour shipping**

SCRAMBER SS SERIES

- 6 precision stainless steel ball bearings
- Cybernetic Frame system (CF)
- Titanium plated anti-twist line roller
- Instant anti-reverse
- Aluminum alloy reel body, rotor and spool
- Balanced anti-twist rotor
- Intelligent Oscillating system (I/O)
- Soft-touch handle knob

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICASS2000R	5.2	10.6	6BB+1RB	28.3 in.	5/225, 6/175, 8/135
TICASS2500R	5.2	10.6	6BB+1RB	28.3 in.	6/220, 8/175, 10/160
TICASS3500R	5.2	14.3	6BB+1RB	31.1 in.	10/220, 12/200, 14/170
TICASS4000R	5.2	14.3	6BB+1RB	31.1 in.	12/260, 14/230, 17/200
TICASS5000R	4.3	22	6BB+1RB	31.1 in.	14/350, 17/290, 18/220
TICASS6000R	4.3	22	6BB+1RB	31.1 in.	17/360, 18/280, 20/220
TICASS7000R	4.1	26.6	6BB+1RB	33.5 in.	18/310, 20/240, 25/200
TICASS8000R	4.1	26.8	6BB+1RB	33.5 in.	20/280, 25/230, 30/200
TICASS10000R	4.1	25.7	6BB+1RB	33.8 in.	25/355, 30/290, 35/245



WASABI WC SERIES

- 8 precision stainless steel rust resistant ball bearings
- One piece aluminum frame CNC machined
- Centrifugal brake system
- Quick remove sideplate
- Forged aluminum alloy handle knob
- Forged aluminum alloy spool
- Instant anti-reverse
- Star drag
- Line out alarm

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICAWC205	5.2	13.3	8BB+1RB	23.2 in.	14/275, 17/210, 20/165



STRIPER LE SERIES

- 8 precision stainless rust resistant ball bearings
- One piece aluminum frame CNC machined
- Centrifugal brake system
- Quick remove sideplate
- Large ultra wear-resisting line guide
- Forged aluminum alloy spool
- Instant anti-reverse
- Star drag
- Line out alarm
- Forged aluminum alloy handle knob

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICAL200	5.2	14.6	8RRB+1RB	23.2 in.	14/275, 17/210, 20/165



ALASKAN AK SERIES

- 4 rust resistant ball bearings and 2 SUS ball bearings
- One piece aluminum frame CNC machined
- Centrifugal brake system
- Quick remove sideplate
- Large ultra wear-resisting line guide
- Forged aluminum alloy spool
- Instant anti-revers
- Star drag
- Line out alarm
- Soft-touch handle knob & clutch bar

No.	Gear Ratio	Wt. (oz.)	Bearings	Line Retrieve Per Turn	Line Cap. (lb-yds)
TICAAK50BLUE	5.2	12	4RRB+2BB(SUS)+1RB	23.2 in.	14/275, 17/210, 20/165
TICAAK51BLUE	5.2	12	4RRB+2BB(SUS)+1RB	23.2 in.	14/275, 17/210, 20/165



Sea Striker® Reels

CORVUS LEVELWIND REEL

No.	Description
SEACC20	2BB - 4.1-1 gear ratio - 310 yds 20# mono
SEACC30	2BB - 4.4-1 gear ratio - 325 yds 20# mono

ARIES SPINNING REELS

No.	Description
SEAAS40	4+1 BB - 5.2-1 gear ratio - 215 yds 10# mono
SEAAS50	4+1 BB - 5.2-1 gear ratio - 300 yds 12# mono
SEAAS60	4+1 BB - 5.2-1 gear ratio - 250 yds 15# mono
SEAAS70	4+1 BB - 4.1-1 gear ratio - 350 yds 20# mono



**Combos are
also available.
Call for models.**