



You don't have to be on the tournament circuit to experience the professional performance of the new Supercaster Pro. Serious fishermen now have the type of tournament winning performance that professional anglers expect with the new Supercaster Pro series. U.S. Reel engineers have designed and fine-tuned the new Pro so that every feature is geared to peak performance. You can fish with absolute confidence with a Pro on your rod, whether it's for club bragging rights or a six-figure payday.

**Specifications**

Sideplate/Body Mat'l	<b>US180PRO</b> Composite
Rotor Material	Hi-Perf. Composite
Main Spool	Forged Aluminum
Spare Spool	Graphite
Spool Diameter	1.8"
# of Ball Bearings	5 ABEC 1 SS +1
Weight (Aluminum Spool)	7.2 oz.
Weight (Spare Spool)	6.8 oz.
Spool Shaft	Stainless Steel
Retrieve Per Handle Turn	26"
Braid Capacities* (Lb./Yd.)	10/213, 20/144
Mono Capacities* (Lb./Yd.)	2/626, 4/331, 6/253, 8/171

**US230PRO**

Composite
Carbon Fiber
Forged Aluminum
Graphite
2.3"
5 ABEC 1 SS +1
8.7 oz.
8.3 oz.
Stainless Steel
29"
20/240, 30/153
6/432, 10/221, 12/205, 14/149

**US250PRO**

Aluminum
Carbon Fiber
Forged Aluminum
Aluminum
2.5"
5 ABEC 1 SS +1
9.9 oz.
9.9 oz.
Stainless Steel
33"
6/647, 10/471, 20/308, 30/211
6/604, 10/314, 12/287, 14/220



\* Yardages are without supplied arbor. Use of arbor significantly reduces line capacity.



This remarkable series represents the Third Generation in the Evolution of W-I-D-E. There's no stopping progress, and nowhere is this fact more boldly stated than in the new 3G series of SuperCaster spinning reels. While U.S. Reel exclusives like the SDS™ Drag remain standard, internal upgrades and new features such as the new EVR-Roll™ line roller make this generation of SuperCasters the best there is! This is a tournament calibre spinning reel that's priced for the weekend angler.

**Specifications**

Sideplate/Body Mat'l	<b>US1803G</b> Composite
Rotor Material	Hi-Perf. Composite
Main Spool	Forged Aluminum
Spare Spool	Graphite
Spool Diameter	1.8"
# of Ball Bearings	5 SS+1
Weight (Aluminum Spool)	6.7 oz.
Weight (Spare Spool)	6.3 oz.
Ball Bearing Type	(5) Stainless Steel +1
Spool Shaft	Stainless Steel
Retrieve Per Handle Turn	26"
EVR-Roll™ Line Roller	Yes
Braid Capacities* (Lb./Yd.)	10/213, 20/144
Mono Capacities* (Lb./Yd.)	2/626, 4/331, 6/253, 8/171

**US2303G**

Composite
Hi-Perf. Composite
Forged Aluminum
Graphite
2.3"
5 SS+1
9.1 oz.
8.8 oz.
(5) Stainless Steel +1
Stainless Steel
29"
20/240, 30/153
6/432, 10/221, 12/205, 14/149

**US2503G**

Aluminum
Hi-Perf. Composite
Forged Aluminum
Aluminum
2.5"
5 SS+1
10.3 oz.
10.3 oz.
(5) Stainless Steel +1
Stainless Steel
33"
Yes
6/647, 10/471, 20/308, 30/211
6/604, 10/314, 12/287, 14/220



\* Yardages are without supplied arbor. Use of arbor significantly reduces line capacity.



This reel Proved that WIDE is the new standard for spinning performance. The SuperCaster SX series re-defined spinning reel design function and performance. The exclusive wide spool greatly enhances casting while reducing twist and allowing a wide range of line tests. Key carbon fiber components, ABEC 1 stainless steel ball bearings and the sealed, quick-starting SDS™ Drag sets a new standard. From meadow stream browns to back country reds, the SX series lets you fish with total confidence.

**Specifications**

Sideplate/Body Mat'l	<b>US180SX</b> Composite
Rotor Material	Hi-Perf. Composite
Main Spool	Forged Aluminum
Spare Spool	Graphite
Spool Diameter	1.8"
# of Ball Bearings	4 ABEC 1 SS+1
Weight (Aluminum Spool)	7.2 oz.
Weight (Spare Spool)	6.8 oz.
Spool Shaft	Stainless Steel
Retrieve Per Handle Turn	26"
Braid Capacities* (Lb./Yd.)	10/213, 20/144
Mono Capacities* (Lb./Yd.)	4/331, 6/253, 8/171

**US230SX**

Composite
Carbon Fiber
Forged Aluminum
Graphite
2.3"
4 ABEC 1 SS+1
8.9 oz.
8.5 oz.
Stainless Steel
29"
20/240, 30/153
6/432, 10/221, 12/205, 14/149

**US240SX**

Aluminum
Carbon Fiber
Forged Aluminum
Aluminum
2.4"
4 ABEC 1 SS+1
9.9 oz.
9.9 oz.
Stainless Steel
31"
20/277, 30/188
6/540, 10/277, 12/254, 14/191



\* Yardages are without supplied arbor. Use of arbor significantly reduces line capacity.



X-hileration! is what you'll X-perience on the first cast and during the first fight with the new SuperCaster X Series. The X-citement continues every time you hit the water with one of these no-frills, but feature-packed reels. From the exclusive SuperCaster wide spool design to the silky two stainless steel ball bearing operation to the rock solid anti-reverse to the smooth Teflon drag, the new X Series of U.S. Reel SuperCaster puts performance on the line for the budget conscious fisherman. And in three sizes, this series is X-actly the ticket for pan-fryers to wall-hangers.

**Specifications**

	<b>US180X</b>	<b>US230X</b>	<b>US240X</b>
Sideplate/Body Mat'l	Composite	Composite	Aluminum
Rotor Material	Composite	Composite	Composite
Main Spool	Forged Aluminum	Forged Aluminum	Forged Aluminum
Spool Diameter	1.8"	2.3"	2.4"
# of Ball Bearings	2	2	2
Weight (Aluminum Spool)	6.9 oz.	9.5 oz.	10.4 oz.
Ball Bearing Type	2 Stainless Steel +1	2 Stainless Steel +1	2 Stainless Steel +1
Spool Shaft	Chrome Steel	Chrome Steel	Chrome Steel
Retrieve Per Handle Turn	26"	29"	31"
Braid Capacities* (Lb./Yd.)	10/213, 20/144	20/240, 30/153	20/277, 30/188
Mono Capacities* (Lb./Yd.)	4/331, 6/253, 8/171	6/432, 10/221, 12/205, 14/149	6/540, 10/277, 12/254, 14/191



\* Yardages are without supplied arbor. Use of arbor significantly reduces line capacity.



Once you fish WIDE you'll never go back! Fish all day without fatigue with a lightweight SuperCaster XL. The exclusive wide spool design maximizes casting distance while minimizing twist, and the InfiStop III™ anti-reverse delivers rock solid hooksets. Set your drag higher and with total confidence with the patent-pending SDS™ Drag that starts quickly and stays steady from the first fight through the last.

**Specifications**

	<b>US180XL</b>	<b>US230XL</b>	<b>US240XL</b>
Sideplate/Body Mat'l	Composite	Composite	Aluminum
Rotor Material	Hi-Perf. Composite	Hi-Perf. Composite	Hi-Perf. Composite
Main Spool	Forged Aluminum	Forged Aluminum	Forged Aluminum
Spare Spool	Graphite	Graphite	Aluminum
Spool Diameter	1.8"	2.3"	2.4"
# of Ball Bearings	4 Stainless Steel +1	4 Stainless Steel +1	4 Stainless Steel +1
Weight (Aluminum Spool)	6.7 oz.	9.5 oz.	10.4 oz.
Weight (Spare Spool)	6.3 oz.	9.1 oz.	10.4 oz.
Spool Shaft	Standard	Standard	Standard
Retrieve Per Handle Turn	26"	29"	31"
Braid Capacities* (Lb./Yd.)	10/213, 20/144	20/240, 30/153	20/277, 30/188
Mono Capacities* (Lb./Yd.)	4/331, 6/253, 8/171	6/432, 10/221, 12/205, 14/191	6/540, 10/277, 12/254, 14/191



\* Yardages are without supplied arbor. Use of arbor significantly reduces line capacity.



Advanced gear System. The Reverse Rotation of the SuperCaster spool required a new gearing mechanism. Most 7 to 1 retrieve reels have a large casing on the main-gear side of the reel that often protrudes down beyond the reel foot. But SuperCaster is able to achieve high speed retrieve with a much more compact assembly that features a new main gear with teeth on the inside to produce a stronger, smoother drive train.

**Specifications**

	<b>USSC1000</b>	<b>USSC1000PRO</b>
Reverse Spool Rotation	Yes	Yes
ABLE™ Levelwind	Yes	Yes
Main Spool	Forged Aluminum	Forged Aluminum
# of Ball Bearings	4	6
Weight	8.3 oz.	8.5 oz.
Ball Bearing Type	(4) ABEC1 SS	(6) ABEC1 SS
Spool Shaft	Stainless Steel	Stainless Steel
Retrieve Ratio	6.6 to 1	7.1 to 1
Retrieve Per Handle Turn	28"	30"
Braid Capacities (Lb./Yd.)	10/221, 20/148	10/221, 20/148
Mono Capacities (Lb./Yd.)	10/144, 12/131, 14/106, 20/74	10/144, 12/131, 14/106, 20/74

