



**16 CARRIER  
SPLICEABLE  
SPECTRA FIBER  
SMALL DIAMETER  
FIBER TECH PROTECTION  
UNIFORMED CONSTRUCTION**



Photo by Pat Ford

**C16 SPLICEABLE - "HOLLOW CORE SUPERBRAID"**

Cortland has again raised the bar with super braid construction and technology. Cortland is proud to offer C16 Spliceable Superbraid. Constructed using high-tech Spectra® fibers in a 16 carrier construction for an extremely small diameter to strength ratio. C16's, 16 carrier braid construction and uniformed pick count (wraps per inch) is the perfect match for allowing you to quickly splice a few feet of mono, while maintaining line strength between the braid and the top shot. Cortland has also treated C16 with their proprietary "FIBER TECH" Superbraid Protection that dramatically increased the braid's durability and ensures consistent performance over time.

**STIFF "SPLICEABLE" SUPER BRAID - Targeted Elongation 4%**

C16 White	Break Strength	Avg. Mono Equiv.	Avg. Dia. In.	Avg. Dia. mm	Avg. Picks/In.
80	18	.020	.508	30	
100	20	.022	.558	23	
130	25	.025	.635	20	
200	50	.031	.787	17	



White

**Spools / Tests:**  
600 Yards - 80, 100, 130, 200  
1200 Yards - 80, 100, 130, 200  
2500 Yards - 80, 100, 130, 200

