

AND LARGER SPOOLS

SH Series

# DYNASPIN

## DYNASPIN SH Series

RRB-Rust Resistant Bearing RB-Roller Bearing

Model No.	Gear Ratio	Weight (oz.)	Bearings	Line Retrieved Handle Turn	Line Capacity (lb-yds)
SH1000	4.5	7.4	8RFB+IRB	22.5in	2-240 3-150 4-120
SH1500	4.5	7.4	8RFB+IRB	22.5in	3-190 4-150 5-120
SH2000	4.6	9.5	8RFB+IRB	26.0in	4-230 5-190 6-150
SH2500	4.6	9.5	8RFB+IRB	26.0in	5-260 6-200 8-160
SH3000	4.6	12.3	8RFB+IRB	29.5in	6-280 8-230 10-200
SH3500	4.6	12.3	8RFB+IRB	29.5in	8-300 10-260 12-230
SH4000	4.6	12.7	8RFB+IRB	31.5in	10-340 12-300 14-250
SH4500	4.6	12.7	8RFB+IRB	31.5in	12-360 14-300 16-260
MC SH5000	4.4	21.5	9RFB+IRB	34.5in	14-400 17-310 20-240
MC SH6000	4.4	21.0	9RFB+IRB	34.5in	20-300 25-240 30-200

Body	Body Cover	Rotor	Spool	CF System	Intelligent Oscillating	Computer Balanced	Reel Bag
AL	GR	GR	AL	■	■	■	■



Rust Resistant Bearing



INSTANT ANTI-REVERSE



COMPUTER BALANCED



INTELLIGENT OSCILLATING SYSTEM



Cybernetic Frame System



ALUMINUM BODY

- ◆ Sealed precision stainless steel rust resistant ball bearings.
- ◆ Intelligent Oscillating system (I/O).
- ◆ Aluminium alloy body and spool.
- ◆ One-way clutch instant anti-reverse roller bearing.
- ◆ Cybernetic Frame system (CF).
- ◆ Balanced rotor.
- ◆ CNC machined aluminum alloy handle.
- ◆ Soft-touch handle knob.
- ◆ Right / left interchangeable handle.
- ◆ With extra spool.



● SH2000



● SH5000

# DYNASPIN

## GH Series

THINNER BODIES

### DYNASPIN GH Series

P-Pearl BL-Blue RRB-Rust Resistant Bearing RB-Roller Bearing

Model No.	Gear Ratio	Weight (oz.)	Bearings	Line Retrieved Handle Turn	Line Capacity (lb-yds)
GH1000	4.5	7.4	6RRB+1RB	22.5in	2-240 3-150 4-120
GH1500	4.5	7.4	6RRB+1RB	22.5in	3-190 4-150 5-120
GH2000	4.6	9.5	6RRB+1RB	26.0in	4-230 5-190 6-150
GH2500	4.6	9.5	6RRB+1RB	26.0in	5-260 6-200 8-160
GH3000	4.6	12.3	6RRB+1RB	29.5in	6-280 8-230 10-200
H3500	4.6	12.3	6RRB+1RB	29.5in	8-300 10-260 12-230
GH4000	4.6	12.7	6RRB+1RB	31.5in	10-340 12-300 14-250
GH4500	4.6	12.7	6RRB+1RB	31.5in	12-360 14-300 16-260
<b>GH5000</b>	4.4	21.5	7RRB+1RB	34.5in	14-400 17-310 20-240
<b>GH6000</b>	4.4	21.0	7RRB+1RB	34.5in	20-300 25-240 30-200

Body	Body Cover	Rotor	Spool	CF System	Intelligent Oscillating	Computer Balanced	Reel Bag
AL	GR	GR	AL	■	■	■	■



Rust Resistant Bearing



INSTANT ANTI-REVERSE



COMPUTER BALANCED



INTELLIGENT OSCILLATING SYSTEM



Cybernetic Frame System



ALUMINUM BODY



● GH2500(P-BL)

- ◆ Sealed precision stainless steel rust resistant ball bearings.
- ◆ Intelligent Oscillating system (I/O).
- ◆ Aluminium alloy body and spool.
- ◆ One-way clutch instant anti-reverse roller bearing.
- ◆ Cybernetic Frame system (CF).
- ◆ Balanced rotor.
- ◆ Soft-touch handle knob.
- ◆ Right / left interchangeable handle.
- ◆ With extra spool.



● GH5000(P-BL)